



**Hydroperfect Intl. Inc.**  
 North America  
 Tel: (905) 791-3388  
 Fax: (905) 791-7322

**POWERPACKS & PUMP/MOTOR**  
 SERIES 2, 3, 4 & 5 PUMPS  
 (NORTH AMERICAN FORMAT)

REVISION 1 - 01/2005



- PUMP SERIES**
- 2
  - 3
  - 4
  - 5

- MOTOR TYPE**
- NO MOTOR 0
  - 0.25 HP A
  - 0.33 HP B
  - 0.50 HP D
  - 0.75 HP G
  - 1.00 HP F
  - 1.50 HP X
  - 2.00 HP Y
  - 3.00 HP W
  - 5.00 HP R
  - OTHER \*

**VOLTAGE**

- NO MOTOR
- 115 / 230
- 115 / 230
- 230 / 460
- 230 / 460
- 575
- 575
- SPECIAL

**MOTOR SPECIAL**

- 3
- 4
- 5
- 6
- 7
- 8
- \*

- PUMP CAPACITY**
- SPECIFY PUMP MODEL  
 REFER TO PUMP CATALOG ####

- PUMP PORTING**
- THREADED PORTS, SAE U
  - FLANGE STYLE, HPI H
  - FLANGE STYLE, BOSCH C

- PUMP OPTIONS**
- NONE, STANDARD L
  - HIGH P RELIEF, INTERNAL X
  - HIGH P RELIEF, EXTERNAL T
  - LOW P RELIEF, INTERNAL V
  - LOW P RELIEF, EXTERNAL W

- SHAFT TYPE**
- KEYED SHAFT C
  - SPLINED SHAFT S

**VALVE CONFIGURATION**

- NONE, P & T PORTS ONLY 20
- SINGLE ACTING CIRCUIT, WITH VNF VF
- FLOW CONTROL, FOR SINGLE ACTING AF
- CETOP 3 - BASEPLATE ONLY 25
- CETOP 3 - 2 POSITION C2
- CETOP 3 - 3 POS, CLOSED CENTRE CC
- CETOP 3 - 3 POS, OPEN CENTRE CO
- CETOP 3 - 3 POS, Y CENTRE CY
- CETOP 3 - 3 POS, TANDEM CENTRE CT
- CETOP 3 - DUAL PO CHECK CP
- CETOP 3 - DUAL FLOW CONTROL CF
- CETOP 3 - DUAL COUNTERBALANCE VALVE CB
- PRESSURE GAUGE PG


**RELIEF VALVE**

- N NOT SEALED

**ACCESSORIES**

- X NONE
- F RETURN FILTER, INTERNAL: 5 mic
- T RETURN FILTER, EXTERNAL: 5 mic
- C OIL COOLER
- A ADDITIONAL RETURN PORT
- \* OTHER

**MOUNTING POSITION**



**RESERVOIR**

- XX NONE
- Qa 6,5 L 1.71 Gal
- Da 12 L 3.17 Gal
- La 20 L 5.28 Gal
- Ma 30 L 7.92 Gal
- Na 44 L 11.6 Gal
- Oa 70 L 18.5 Gal
- \*\* SPECIAL

**VOLTAGE - VALVES**

- X NOT APPLICABLE
- 2 12 VDC
- 4 24 VDC
- 5 24 VAC
- 1 115 VAC
- 3 230 VAC
- \* SPECIAL